

**Listing of Claims:**

Claim 1 (previously presented): An apparatus for use in parallel reaction of materials, comprising:

a base having a plurality of reaction wells formed therein; and

a sealing device positioned over the reaction wells for individually sealing each of the reaction wells;

one of the sealing device and the base having chamfered ridges extending generally around a periphery of each of said plurality of reaction wells, the other of the sealing device and the base having a metal contact surface formed from a material softer than a material of the chamfered ridges to create a knife-edge seal between the sealing device and the base when the sealing device and the base are forced into contact with one another.

Claim 2 (original): The apparatus of claim 1 wherein the base and the sealing device are both formed from metal.

Claim 3 (original): The apparatus of claim 1 wherein the base is formed from a material harder than the sealing device.

Claim 4 (original): The apparatus of claim 3 wherein the base is formed from stainless steel.

Claim 5 (original): The apparatus of claim 3 wherein the sealing device is formed from a material selected from the group consisting of aluminum, tin, copper, and nickel.

Claim 6 (original): The apparatus of claim 1 further comprising a cover positioned over the sealing device.

Claim 7 (original): The apparatus of claim 6 wherein the cover and the base each comprise a plurality of aligned openings for receiving bolts used to attach the cover to the base and force the sealing device into contact with the base.

Claim 8 (original): The apparatus of claim 1 wherein the chamfered ridges are machined into the base.

Claim 9 (original): The apparatus of claim 1 wherein said plurality of reaction wells comprises 100 or more reaction wells.

Claim 10 (original): The apparatus of claim 1 wherein each of said plurality of reaction wells comprises a closed lower end and an open upper end for receiving components of the reaction.

Claim 11 (cancelled)

Claim 12 (original): The apparatus of claim 1 wherein each of said plurality of reaction wells has an internal volume of approximately 10 to 500  $\mu\text{l}$ .

Claim 13 (original): The apparatus of claim 1 wherein the base is generally rectangular in shape.

Claim 14 (original): The apparatus of claim 1 wherein the base is generally circular in shape.

Claims 15-18 (canceled).

Claim 19 (previously presented): The apparatus of claim 1 wherein the sealing device is defined by a cover configured for attachment to the base.

Claim 20 (canceled).

Claim 21 (previously presented): The apparatus of claim 1 wherein the sealing device comprises a plurality of sealing caps for sealing each of said plurality of reaction wells and the chamfered ridges are formed in an end of the sealing caps and wherein the sealing device is formed from a material harder than the base.

Claim 22 (cancelled)

Claim 23 (original): The apparatus of claim 21 wherein the contact surface of the base comprises a plurality of gaskets each positioned around the periphery of one of said plurality of reaction wells.

Claim 24 (previously presented): The apparatus of claim 23 wherein the gasket is formed from a material softer than a material of the sealing caps.

Claim 25 (previously presented): The apparatus of claim 24 wherein the gasket is formed from copper and the sealing caps are formed from steel.

Claim 26 (previously presented): The apparatus of claim 21 wherein the sealing caps are spring biased against the base.

Claim 27 (original): The apparatus of claim 21 further comprising a plurality of flow through vessels positioned within the reaction wells.

Claim 28 (original): The apparatus of claim 1 wherein the apparatus is configured for use as a batch reactor.

Claim 29 (original): The apparatus of claim 1 wherein the apparatus is configured for use as a fixed bed reactor.

Claims 30-34 (canceled).